

metrolite

Diesel LED Light Tower



DLT C-Series 4kW & 8kW

COLD WEATHER PACKAGE

The **DLT C-Series** light towers are designed to be reliable and tough in any environment while consistently delivering efficient and effective lighting to your jobsite.

The low fuel consumption of the DLT C-Series provides considerable savings compared to traditional 6 and 8kW light towers.

Features:

- Efficient LED Lamps
- Deep Sea Electronics controller
- Fork pockets and single point lift
- Automatic dawn to dusk sensor
- Extended service intervals of 750 hours between oil changes

Specifications	DLT-4C+	DLT-8C
L x W x H	63 in x 55 in x 92.5 in	97 in x 56.5 in x 91 in
Total Weight w/o Fuel	1,316 lbs	1907 lbs
Floodlights	4 x 320 W LED	4 x 350 W LED
Total Lumen	166,200 lm	189,000 lm
Mast Height	23 ft (7 m)	23 ft (7m)
Max Wind Rating	100 kph (62 mph)	100 kph (62 mph)
Power (1.0 PF)	4.2 kW	8 kW
Electrical Receptacles	1 x 115V15A Outlet 1 x 115V15A Inlet	2 x 20A GFCI socket 1 x 30A twist lock socket 1 x 30A twist lock inlet
Generator End	Linz	Linz / NSM
Engine	Kohler KDW702	Mitsubishi L3E
Sound Level	65 dB(A) at 7 meters	60 dB(A) at 7 meters
Fuel	Diesel	Diesel
Fuel Tank Capacity	120 L (32 US gal)	170 L (45 US gal)
Fuel Consumption (lights only)	0.55 L/hr (0.15 gal/hr)	1.1 L/hr (0.29 gal/hr)
Run Time (lights only)	218 hrs	152 hrs
Secondary Fluid Containment	110%	110%

All specifications are subject to change without prior notice.

AXIOM
EQUIPMENT GROUP
EXPECT HIGHER STANDARDS ON SITE

Call (844) 732 9466
www.axiomequipmentgroup.com